

S9 coupé

100-150 HP

Ø max. 9 cm [3.5 inch]

Heavy duty flail mulcher with side shift linkage and compact profile

The S9 series machines mulch grass, vegetation and prunings up to 9 cm [3.5"] in diameter. The adjustable rear hood allows you to alter the degree of mulching.

The side shift is linear and works even while the machine is mowing, with hydraulic control from the tractor seat.

The low and compact profil of the **S9 coupé** allows the machine to mulch very close to the crop and it therefore can work directly under the canopy without damaging fruit.

Standard version and characteristics

- > Mulches grass and brush up to 9 cm [3.5"]Ø
- > Working speed 3-10 km/h
- > 3 point rear linkage cat. 2
- > Linear hydraulic side shift
- > 1000 rpm gearbox with freewheel and through shaft
- > Belt transmission
- > Adjustable rear hood with rubber protection
- > Front protection with chains
- > Support roller 193 mm Ø
- > Rotor with SMO flails

Optional configuration and accessories

- > 540 rpm gearbox
- > Belt cover on the right (working left)
- > Front protection with metal flaps instead of chains
- > Roller scraper



 www.youtube.com/seppimulcher

Tools




SMO
Flails

Specifications · S9 coupé				Nominal tractor power 100-150 HP				
Working width		cm [inch]	200 [79]	225 [89]	250 [98]	275 [108]	300 [118]	
Side shift from	 max to the left	L R cm [inch]	126 74 [50 29]	126 99 [50 40]	126 124 [50 50]	126 149 [50 59]	126 174 [50 70]	
middle of tractor	 max to the right	L R cm [inch]	59 141 [23 56]	59 166 [50 65]	59 191 [23 75]	59 216 [23 85]	59 241 [23 96]	
Overall width		cm [inch]	215 [85]	240 [95]	265 [100]	290 [114]	315 [124]	
Depth		cm [inch]	112 [44]	112 [44]	112 [44]	112 [44]	112 [44]	
Height		cm [inch]	105 [41]	105 [41]	105 [41]	105 [41]	105 [41]	
Weight · base value		kg	880 [1,940]	960 [2,116]	1.025 [2,260]	1.110 [2,447]	1.210 [2,668]	
Belts		Anzahl	5	5	5	5	5	
Flails		Anzahl	21	24	27	27	30	


S9 coupé · features

Strong and robust casing made of high-tensile steel, with replaceable wear plates.



The power belt chassis is very compact - it allows the machine to work under low canopy close to the trunk


Hydraulic side shift:
linear up to 68 cm [27"]




Adjustable hood to set the degree of mulching




Strong roller with double tapered bearing unit for a long life, the large diameter improves mulching on uneven ground.



Due to the close position of the roller to the rotor, the rotating flails clean the roller, and the cut material is evenly distributed over the top.



Rotor with SMW flails
Low power consumption at maximum throughput with helix rotor technology



Replaceable tempered counter cutters inside the casing provide a perfect result when mulching.

