


MIDIFORST

max. 25 cm Ø  80-130 HP

Compact forestry mulcher with high performance

The MIDIFORST forestry mulcher is ideal for a wide range of jobs. In forestry for the care of woodland and forest paths, electricity and gas pipelines, cleaning after the harvesting of wood and for the construction of fire breaks.

In agriculture the renewal of existing fruit and wine plants, berry plants and further landscape maintenance.


Standard version and specifications

- > Mulches bushes and wood up to 25 cm [9.8"]Ø
- > Working speed 0-5 km/h
- > 3 point rear linkage cat. 2 central fixed
- > 1000 rpm gearbox with freewheel
- > Belt transmission
- > Hydraulically operated hood
- > Reinforced skids, adjustable in height
- > Front and rear protection with chains
- > Tempered counter cutters
- > Standard rotor: Combination of fixed hammers with tungsten carbide inserts MINI DUO and MONO PROTECT EXTREME

Optional configuration and accessories

- > CUT CONTROL rotor with MINI DUO
- > CUT CONTROL rotor with MINI BLADE
- > Front attachment
- > 540 rpm gearbox
- > Centrifugal clutch
- > Guard frame
- > Rake hood
- > Support roller (instead of skids)



 www.youtube.com/seppimulcher

Specifications · MIDIFORST		Tractor 80-130 HP		
Working width	175 cm [69"]	200 cm [79"]	225 cm [89"]	
Overall width	204 cm [80"]	229 cm [90"]	254 cm [100"]	
Depth	112 cm [44"]	112 cm [44"]	112 cm [44"]	
Height	120 cm [47"]	120 cm [47"]	120 cm [47"]	
Weight (base value w/o options)	1.240 kg [2730lb]	1.360 kg [3000lb]	1.470 kg [3240lb]	
Belts	5	5	5	
Fixed hammers · standard	38+2	42+2	46+2	
Fixed hammers · OPT CUT CONTROL	40	44	48	

Tools

	+		MINI DUO + LATERAL EXTREME
			MINI-DUO + CUT CONTROL
			MINI BLADE + CUT CONTROL

MIDIFORST · Specifications

Compact strong forestry cutter for medium sized tractors
with reinforced chassis, welded belt protection and lateral deflectors.

