

MAX 75 le

le = linear extension
rc = radio controlled

... manages dense vegetation even on steep terrain

This radio-controlled tracked vehicle is built to take on the toughest challenges with an impressive output of 75 hp. Powered by a high-performance 4-cylinder turbo diesel engine, this vehicle guarantees maximum efficiency. Thanks to the optimal center of gravity, the vehicle's stability is always guaranteed, even on difficult terrain. With a track width of up to 245 cm, slopes of up to 55° can be negotiated with ease. Due to its generous hydraulic performance, the vehicle is ideally equipped to deliver the necessary torque even in the most demanding situations. In terms of mobility and performance, the MAX 75 le is the perfect vehicle for both agriculture and forestry.

MAX 75 le

Tracked Tool Carrier

- > Lifting linkage with assisted **FLOAT**
- > Underbody protection and steel covering
- > Hydraulic adjustment of the vehicle width 800 mm (2x400 mm) [32 inch = 2x16 inch]
- > Active **AUTO TRACK TENSION** system
- > Stability and traction due to superior track profile with high ground contact and LGP undercarriage **HIGH GRIP**
- > Automatic reversible fan
- > Remote control with display 2.4 Ghz - 160 m range
- > 4 Cylinder T4F/STAGE V Perkins engine 2200 cc
- > Closed circuit triple piston pump with variable displacement, plus additional gear pump

Options:

- Bio Oil instead of standard oil
- Steeltracks instead of rubber
- Forestry rear protection

H5 rc 175

Flail Mulcher

- > Mulches grass+brush up to 5 cm [2"]Ø
- > Variable displacement motor 22-45 cm³ with relief valve
- > Helical rotor with SMW flails

MICROFORST rc 155

Forestry Mulcher

- > Mulches wood up to 15 cm [6"] Ø
- > 30 cc PISTON MOTOR with flushing valve
- > Helical rotor with CUT CONTROL and fixed hammers MINI DUO alternative MINI BLADE

MICROSOIL rc 105

Stone crusher

- > Crushes stones up to 15 cm [6"] Ø tills the soil as deep as 10 cm [4"]
- > Automatic variable displacement motor 60-80 cm³ M-BOOST
- > Helical rotor with fixed CARBIDE hammers



[YouTube www.youtube.com/seppimulcher](https://www.youtube.com/seppimulcher)

Specifications	MAX 75 le	H5 rc	MICROFORST rc	MICROSOIL rc
Rotor working width	-	175 cm [69 inch]	155 cm [61 inch]	105 cm [41 inch]
Overall width	165-245 cm [65-96 inch]	187 cm [74 inch]	174 cm [69 inch]	126 cm [50 inch]
Depth	260 cm [102 inch]	82 cm [32 inch]	86 cm [34 inch]	93 cm [37 inch]
Height	125 cm [49 inch]	80 cm [31 inch]	76 cm [30 inch]	75 cm [30 inch]
Weight	2.200 kg [4,850 lbs]	520 kg [1,150 lbs]	490 kg [1,080 lbs]	520 kg [1,150 lbs]
Helical rotor	-	18 flails	33 hammers CUT CONTROL	21 CARBIDE hammers

Powerful & High-Performance Hydraulic Drive


MAX 75 le		DIESEL FUEL TANK	HYDRAULIC FLUID TANK	MULCHER HYDRAULICS		TRACKS HYDRAULICS		SECONDARY HYDRAULICS	
HP	kW	l [gallon]	l [gallon]	bar [psi]	l/min [gpm]	bar [psi]	l/min [gpm]	bar [psi]	l/min [gpm]
75	55	39 [10]	72 [19]	380 [5,500]	93 [25]	400 [5,800]	154 [41]	200 [2,900]	15 [4]

EXTENDABLE UNDERCARRIAGE
to adjust the width of the individual tracks.
Powerful when climbing and crossing extreme
slopes. With the enlarged undercarriage, the
mulcher works more efficiently and precisely
on extreme and uneven grades.

Hydraulic system
with self-tensioning tracks





Radio control with graphic display
controls and monitors all functions
in a frequency range of 2.4 GHz
at a range of up to 160m (500')



MAX 75 le - pictured here with MICROFORST rc 155

The track width can be extended
by 40 cm on each side to a total of 245 cm.



Stability and grip of the vehicle
on difficult terrain up to 55° slopes,
under optimal conditions