

SMWA rev cf

30-90 HP Ø max. 5 cm [2 inch]

Reversible linkage for front and rear

Agriculture or greenspace maintenance? All easy ...
– the mulchers of the SMW series mulch grass, prunings and bushes up to 5 cm [2"] in diameter.

The SMWA rev cf standard version has manual side shift with a two position bolt-on hitch: central and 17 cm [6.7"] to the right.

Standard version and characteristics

- > Mulches grass and brush up to 5 cm [2"]Ø
- > Working speed 3-10 km/h
- > 3 point linkage cat. 1&2 reversible
- > Side shift with 2 positions: central and 17 cm [6.7"] to the right
- > 540 rpm gearbox with freewheel and through shaft
- > Belt transmission
- > Adjustable rear hood with rubber protection
- > Front protection with metal flaps
- > Support roller 152 mm Ø
- > Standard rotor with SMW flails

Optional configuration and accessories

- > Rotor with Y flails
- > 750 or 1000 rpm gearbox
- > Gearbox with automatic inverter and double freewheel
- > Additional 3-point linkage
- > Front attachment
- > Hood with rakes
- > Metal front wheels
- > Front protection with chains instead of metal flaps
- > Additional front rubber flap
- > Roller scraper
- > Attachments for undercanopy maintenance (details see separate brochure)



[YouTube www.youtube.com/seppimulcher](https://www.youtube.com/seppimulcher)

Tools



Flails
SMW



Flails
Y DUO

Specifications · SMWA rev cf

| | | 115 [45] | 125 [49] | 135 [53] | 145 [57] | 155 [61] | 175 [69] | 200 [79] | 225 [89] |
|-----------------------|-----------|-----------|-----------|-----------|-----------|----------|-----------|-----------|-----------|
| Working width | cm [inch] | 115 [45] | 125 [49] | 135 [53] | 145 [57] | 155 [61] | 175 [69] | 200 [79] | 225 [89] |
| Overall width | cm [inch] | 127 [50] | 137 [54] | 147 [58] | 157 [62] | 167 [66] | 187 [74] | 212 [84] | 237 [93] |
| Depth | cm [inch] | 90 [35] | 90 [35] | 90 [35] | 90 [35] | 90 [35] | 90 [35] | 90 [35] | 90 [35] |
| Height | cm [inch] | 95 [37] | 95 [37] | 95 [37] | 95 [37] | 95 [37] | 95 [37] | 95 [37] | 95 [37] |
| Weight (base value) | kg [lb] | 345 [760] | 355 [780] | 385 [850] | 415 [910] | 440[970] | 485[1070] | 515[1140] | 535[1180] |
| Belts | qty | 3 | 3 | 3 | 3 | 3 | 4 | 4 | 4 |
| Flails | qty | 12 | 12 | 12 | 15 | 15 | 18 | 21 | 24 |
| Y flails | qty | 21 | 24 | 24 | 27 | 27 | 33 | 39 | 45 |
| Nominal tractor power | HP | 30-65 | 30-65 | 30-65 | 30-65 | 30-65 | 40-90 | 40-90 | 40-90 |

SMWA rev cf · features

Robust chassis made of high tensile steel.

S420

Gearbox with freewheel and through shaft for front and rear attachment
FR FRONT&REAR

side shift: manual by 2 positions 17 cm [6.7 inch]

Metal front wheels (option)

Adjustable hood to set the degree of mulching
M-FLAP

Support roller, adjustable in height Reinforced bearing and roller

Standard rotor with SMW flails Low power consumption at maximum throughput with HELIX ROTOR technology
HELIX ROTOR

Optional rotor with Y flails

Tempered counter cutters for a perfect mulching result
2 COUNTER CUTTERS