

SMO rev cf

50-120 HP Ø max. 7 cm [2.8 inch]

The expert among the lightweight mulchers with reversible linkage

Road sides, meadows, pastures – the SMO machines satisfy the needs of professionals in the most varied situations with an even clean cut.

The machines of this series mulch grass and brushwood up to 7 cm in diameter.

The model **SMO rev cf** has a central 3-point linkage. The mulcher is reversible and can be driven in both direction - front and rear.

Standard version and characteristics

- > Mulches grass and brush up to 7 cm [2.8"]Ø
- > Working speed 3-10 km/h
- > 3 point linkage cat. 2 reversible
- > 1000 rpm gearbox with freewheel and through shaft
- > Belt transmission
- > Adjustable rear hood with rubber protection
- > Front protection with metal flaps
- > Support roller 152 mm Ø
- > Standard rotor with SMO flails

Optional configuration and accessories

- > Rotor with Y flails
- > 540 rpm gearbox
- > Gearbox with automatic inverter and double freewheel
- > Additional 3-point linkage
- > Front attachment
- > Hood with rakes
- > Front protection with chains instead of metal flaps
- > Additional front rubber flap
- > Metal front wheels
- > Rubber wheels instead of roller
- > Roller scraper
- > Attachments for undercanopy maintenance (details see separate brochure)



www.youtube.com/seppimulcher

Tools



Specifications • SMO rev cf

		150 [59]	175 [69]	200 [79]	225 [89]	250 [98]
Working width	cm [inch]	150 [59]	175 [69]	200 [79]	225 [89]	250 [98]
Overall width	cm [inch]	165 [65]	190 [75]	215 [85]	240 [95]	265 [100]
Depth	cm [inch]	120 [47]	120 [47]	120 [47]	120 [47]	120 [47]
Height	cm [inch]	120 [47]	120 [47]	120 [47]	120 [47]	120 [47]
Weight (base value)	kg [lb]	480 [1,050]	550 [1,210]	600 [1,310]	650 [1,430]	710 [1,560]
Belts	qty	4	4	4	5	5
Flails	qty	15	18	21	24	27
Y flails	qty	27	33	39	45	x
Nominal tractor power	HP	50-100	50-100	50-100	50-120	50-120

S420 rev cf · features

Robust chassis made of high tensile steel.

S420

Adjustable hood to set the degree of mulching
M-FLAP

Gearbox for front and rear attachment
FR FRONTREAR

Rake hood complete with rakes (option)

Metal front wheels (option)

Adjustable support roller, Reinforced bearing and roller

Standard rotor with SMW/SMO flails

Optional rotor with Y flails

Tempered counter cutters for a perfect mulching result
2 COUNTER CUTTERS

Rubber gauge wheels for uneven ground (instead of roller)

Low power consumption at maximum throughput with HELIX ROTOR technology
HELIX ROTOR