# STARFORST hyd

200-420 bar | 200-520 l/min

### STARFORST hyd is a compact mulcher of the highest performance class

This machine features an aggressive rotor with efficient tungsten carbide tipped hammers. The exposed position of the rotor makes it easier to grasp material. The hydraulic STARFORST is ideal for land clearing and ROW maintenance like foresty management, cleaning after felling operations or power line maintenance.

It mulches wood up to 40 cm [16 inch] in diameter. There are different types of guard frames to choose from for felling operations and to protect the tractor.

# Standard version and specifications

- > Mulches wood up to 40 cm [16"] Ø
- > Working speed 0-5 km/h
- > Universal attachment interface
- > Dual side belt transmission
- with CARBONCHAIN gear belts
  > Hydraulically operated hood
- > Chain protection
- > Chassis made of high tensile steel
- > Tempered counter cutters
- > Supporting skids
- Rotor with fixed hammers
   MINI DUO and lateral EXTREME

# Optional configuration and accessories

- Rotor with fixed hammers MONO HIT V-LOCK and lateral EXTREME
- > Interface plates for loaders
- > Hydraulic block with pressure relief valve and internal hoses
- > Motors with relief valve
- > M-BOOST automatic variable displacement motors 2x 70-110 or 2x 110-160 cm<sup>3</sup>
- Mechanical or hydraulic guard frame

YouTube www.youtube.com/seppimulcher

## Overall width adapted to road traffic regulations for an optimal use of the working width!

Specifications • STARFORST hyd			
Working width	210 cm [83"]	235 cm [93"]	260 cm [102"]
Overall width	248 cm [98"]	273 cm [107"]	298 cm [117"]
Depth	122 cm [48"]	122 cm [48"]	122 cm [48"]
Height	117 cm [46"]	117 cm [46"]	117 cm [46"]
Weight (base value w/o options)	2.860 kg [6,300lb]	3.000 kg [6,610lb]	3.170 kg [6,990lb]
Belts	2 x 5	2 x 5	2 x 5
MINI DUO + EXTREME	43+2	48+2	53+2
MONO HIT V-LOCK + EXTREME	61+2	68+2	75+2

# Image: Second system of the second system

TOOLS

The information in this document is intended as a guide only. SEPPI M. may change their products or their specifications at any time without any obligation of previous notice.

M-BOOST

### High-performance hydraulic drive

The powerful STARFORST hyd with double drive adapts to tractors with hydraulic flow rates between 200 and 520 l/min. The mulcher is available with the powerful and efficient M-BOOST motor which delivers 40% more torgue than standard motors.

### HYDRAULIC DRIVE

Pressure	200-420 bar [3,000-6,090 psi]
Required hydraulic flow	200-520 l/min [53 - 137 gpm]
Required hydraulic hoses	3 (pressure, return, drainage)
Case drain pressure	max. 5 bar
REQUIRED HYDRAULIC HOSES	
Hydraulically operated hood	1 double acting
Hydraulic guard frame	1 double acting



bolt-on rotor shaft

with fixed carbide hammers for mulching wood and soil cultivation

wear-resistant steel plates 5 rows of tempered counter cutters for a perfect mulching result