

## MINIFORST cl

200-350 bar | 90-190 l/min

## MINIFORST cl hydraulic transmission mulchers: compact & powerful for compact loaders

These forestry mulchers for skid steers are suitable for forestry work as well as the most demanding applications in landscaping and maintaining areas in which prunings, stumps and wood must be eliminated.

Assembled on a compact loader,

they reach hard-to-access areas with great ease.

## Standard version and specifications

- > Mulches wood up to 20 cm [8"]  $\emptyset$
- > Working speed 0-5 km/h
- > Chassis made of high tensile steel \$420
- > SAE skid steer attachment interface
- > Belt transmission
- > Pressure gauge
- > Hydraulically operated hood
- > Rear chain protection
- > Reinforced support skids, adjustable in height
- > Rotor with tungsten CARBIDE inserts hammers MINI DUO; anti-wear hammer support
- > 5 rows of tempered COUNTER CUTTERS (3 chassis, 2 hood)

# Optional configuration and accessories

- > CUT CONTROL rotor with MINI DUO
- > CUT CONTROL rotor with MINI BLADE
- > Electric valve for hood control with controls
- > Without hood
- > Guard frame
- > Variable displacement motor with relief valve
- > 1/2" polycarbonate impact resistant shield for loader. Replaces original glass shield. Excluding installation.







**☑ YouTube** www.youtube.com/seppimulcher

#### Fields of application

- > Vegetation management in forestry
- > Right of way ROW and roadside maintenance
- > Land clearing and reclamation
- > Site preparation
- > Maintaining of power and communication lines

Specifications · MINIFORST cl				
Working width	cm [inch]	150 [59]	175 [69]	200 [79]
Overall width	cm [inch]	175 [69]	200 [79]	225 [89]
Depth	cm [inch]	99 [39]	99 [39]	99 [39]
Height	cm [inch]	86 [34]	86 [34]	86 [34]
Weight · base value w/o options	kg [lb]	1.055 [2,326]	1.140 [2,513]	1.265 [2,789]
Belts · depending on engine power	qty	4 (5)	4 (5)	4 (5)
MINI-DUO	qty	30	33	36

# MINI-DUO MINI-DUO + CUT CONTROL MINI BLADE +

**CUT CONTROL** 

#### High-performance hydraulic drive



(or OPT-158: electric valve for hood control with controls)



The powerful transmission of the **MINIFORST cl** is compatible with hydraulic systems with flow rates of 90 to 190 l/min and is available with different types of hydraulic motors. The most powerful and efficient motor, the M-BOOST motor, delivers 40% more torque than standard motors.

Your SEPPI M. dealer will help you choose the optimum motor for your application.

HYDRAULIC DRIVE		
HYDRAULIC DRIVE		
Pressure	200-350 bar [3,000-5,075 psi]	
Required hydraulic flow	90-190 l/min [24-50 gpm]	
Required hydraulic hoses	3 (pressure, return, drainage)	
Case drain pressure	max. 1.5 bar	
REQUIRED HYDRAULIC FITTINGS		
	1 double acting	

Hydraulic hood

